

TPC185-A28

The entire panel PC utilizes a self-developed industrial motherboard with an integrated independent NPU, offering 1 TOPS of AI computing power and supporting lightweight AI application development. Its 3mm ultra-thin front panel seamlessly fits various types of cabinets. The device excels in anti-interference and thermal performance, capable of withstanding harsh working conditions such as extreme temperatures, oil, dust, and vibrations.

Features

- 3mm Super Thin Front Bezel, Best for Embedded Cabinet.
- Supports wide temperature and wide voltage operation.
- Self-developed ARM architecture industrial motherboard
- RK3568, 4-core 64-bit Cortex-A55, 2.0GHz main frequency
- Built-in independent NPU with 1TOPS AI computing power
- Support secondary development and upgrade customization



Model

Product size	18.5"
Non-touch	TPC185-A2800
Capacitive touch	TPC185-A2810
Resistive touch	TPC185-A2820

I/O Interface



Specification

Screen Parameter

Display type	18.5" TFT LCD screen
MAX.resolution	1920*1080 (16:9)
Viewing angle(H/V)	89/89/89/89 (L/R/U/D)
Luminance (cd/m²)	270 cd/m²
Contrast ratio	1000:1

Touch Parameter

Touchscreen	Projection capacitive touch 10-point multi touch	Resistive touch single point	Non-touch
Light transmission	≥88%	≥78%	≥92%
Controller	USB (COM customized)	USB (COM customized)	/


Power Parameter

Power input	DC 12V-36V
Power adapter	24V/2.5A

Configuration

CPU	RK3568, Quad-Core/4-Wire 2.0GHz CPU
Memory/RAM	2GB (Optional 4GB/8GB)
Storage	32GB eMMC (Optional 64GB/128GB/256GB)
NPU	Built-in NPU with 1TOPS AI computing power
Operating system	Android12/14, Linux5.10/Ubuntu20.04/Ubuntu22.04/Debian11

Dimension



Physical Characteristic

Overall dimensions	W486.5x H307.4x D58mm
Installation size	W469.7 x H290.6mm
Material	Aluminum alloy
Color	Black, optional silve
Installation	Supports Panel-mount/Wall-embedded/Wall-mounted/Desktop/Folding mounting/VESA mount/Suspended mounting, etc.

Interface Parameter

PowerSW	1*PowerSW
Power interface	3.81-2P Phoenix Terminal (optional upgrade to DC 2.0*1).
Phoenix terminal	3.5-12P Phoenix terminals (2321/4851/CAN1/NC4).
USB	4*USB (2*USB2.0, 2*USB3.0)
TF	1*TF card standard interface
SIM	1*SIM card slot (should be work with 3G/4G module)
HDMI	1*HDMI output, up to 4K
Ethernet	1*LAN, 10M/100M/1000M adaptive Ethernet, 3G/4G customized
Audio	1*Audio I/O, Support audio input and output
Serial port	1*COM (The default is RS232, optional RS485/RS422)
UBOOT	1*UBOOT
Wi-Fi antenna	1*Wi-Fi antenna
Grounding	1*GND
Speaker	2*(8Ω2W)

Reliability Parameter

Operating temperature	-10°C~60°C (-20°C~70°C can be customized)
Storage temperature	-20°C~70°C
Relative humidity	95% non-condensing